

Bazarr



Bazarr is a companion application to Sonarr and Radarr. It manages and downloads subtitles based on your requirements. You define your preferences by TV show or movie and Bazarr takes care of everything for you.

Be aware that Bazarr doesn't scan disk to detect series and movies: It only takes care of the series and movies that are indexed in Sonarr and Radarr.

The screenshot shows the Bazarr web interface. At the top, there is a search bar and a 'Scan Disk' button. The sidebar on the left contains navigation options: Series, Movies, History, Blacklist, Wanted, Settings, and System. The main content area displays the 'Better Call Saul' series page. The series title is 'Better Call Saul', and it shows 10 files in English with standard subtitles. Below the series overview, there is a table of episodes for Season 5.

Episode	Title	Existing Subtitles	Missing Subtitles	Manual Search	Manual Upload	Tools
Season 5						
10	Something Unforgivable	en				
9	Bad Choice Road	en				
8	Bagman	en				
7	JMM	en				
6	Wexler v. Goodman	en				
5	Dedicado a Max	en				
4	Namaste	en				
3	The Guy for This	en				
2	50% Off	en				
1	Music Man	en				

Installation

There are several platforms on which you can install Bazarr. This install is focused on the docker container method of installation since that is my primary way to handle most server applications.

If you do not want to install via a container, the other installation methods for Bazarr can be found on the [official Bazarr wiki](#).

Running Bazarr as a container

Basic examples for getting this image running as a container. The image I am using here is maintained by linuxserver.io

You CANNOT store your config directory over an NFS share as it is unsupported by SQLITE. You will receive a locked database error.

Docker Compose

```
---
version: "2"
services:
  bazarr:
    image: linuxserver/bazarr:1.2.0
    container_name: bazarr
    restart: unless-stopped
    environment:
      - UMASK_SET # Control permissions of files and directories created by Bazarr
      - TZ # Specify a timezone to use EG Europe/London.
      - PUID # ID of user to take ownership of application/files
      - PGID # GID of user to take ownership of application/files
    volumes:
      - /host/path/to/tv:/tv # Location of your TV Shows
      - /host/path/to/movies:/movies # Location of your movies
      - /host/path/to/config:/config # Bazarr data
    ports:
      - 6767:6767/tcp # Allows HTTP access to the internal webserver.
```

CLI

```
docker create \
  --name=bazarr \
  -e UMASK_SET `# Control permissions of files and directories created by Bazarr` \
  -e TZ `# Specify a timezone to use EG Europe/London.` \
  -e PUID `# ID of user to take ownership of application/files` \
  -e PGID `# GID of user to take ownership of application/files` \
  -v /host/path/to/tv:/tv `# Location of your TV Shows` \
  -v /host/path/to/movies:/movies `# Location of your movies` \
  -v /host/path/to/config:/config `# Bazarr data` \
  -p 6767:6767/tcp `# Allows HTTP access to the internal webserver.` \
```

```
--restart unless-stopped \  
linuxserver/bazarr:1.2.0
```

Revision #6

Created 2023-03-22 05:58:46 UTC by Tim

Updated 2023-04-19 23:04:26 UTC by Tim